

D5 SERIES



The thirst quenchers!™

**3 YEAR
WARRANTY**

- ✓ The most reliable POU cooler on the market
- ✓ Available in bench top or floor standing
- ✓ Connects to mains water supply
- ✓ Hot & Cold or Cool & Cold models available
- ✓ HUGE 14.3L Cold Tank
- ✓ Compatible with most Inline Filter Systems
- ✓ Easy to clean and sanitise
- ✓ 36 Month Comprehensive Warranty



**QUALITY &
PERFORMANCE
PROVEN OVER
20 YEARS!**



D5 SERIES

GENERAL FEATURES

Waterworks™ has been leading the way with POU water coolers since introducing the D5 series, over 20 years ago. This model has often been “copied” but none have been able to equal or better the quality and longevity of the Waterworks™ D5.

COLD TANK: Huge 14.3 litre high density polypropylene tank. The tank is tough, rustproof and is easy to clean with its large radius.

HOT TANK: 1.8 litre, type 304 stainless steel with 500 watt sheathed heater ensures temperature control. On/off switch is easily accessible at the back of the unit.

CABINET: Gloss Cloud White colour. Top and front panels are moulded UV treated ABS. Side panels are zinc coated steel sheets, covered in polymer polyester resin.

TAPS: NSF approved, durable polypropylene lever type taps with self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model. Optional push taps now available.

FLOAT ASSEMBLY: One stage polyethylene float system maintains the water level and shuts off when full.

TWIST & TURN TWIN FILTRATION

SEDIMENT CARTRIDGE

- Flow rate 2L per minute
- 5 Micron Polypropylene pre filter for the removal of dirt sediment, rust and particles.
- Filter replacement - 1900L or 6 months. Which ever occurs first.



CARBON BLOCK

- 5 Micron Silver impregnated carbon block for chemical, taste and odour removal.
- Flow rate 2L per minute
- Filter replacement - 1900L or 6 months. Which ever occurs first

TRIPLE FILTRATION OPTION ALSO AVAILABLE



Waterworks Australia

ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157

Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled with no moving parts.

PERFORMANCE

Tap 1 Approx. 4 - 10°C
Tap 2 Room Temperature
Hot tap Approx. 84 - 89°C

CAPACITY

ROOM TEMP	150ML CUPS/HR AT 10°C	LITRES/HR AT 10°C
21°C	44	6.6
27°C	32	4.8
32°C	18	2.7

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
D5C	19kg	D5CH	21kg	33cm	33cm	115cm
SD5C	16kg	SD5CH	18kg	33cm	33cm	70cm

INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

WARRANTY

The Waterworks™ D5 series is covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of origina

Distributed by...

Awesome Water Mackay

0401 441 291

www.awesomewatermackay.com

info@awesomewatermackay.com



Phone (07) 3390 3777

Email sales@waterworksaustralia.com

www.waterworksaustralia.com