

D26 SERIES



The thirst quenchers!™



- ✓ Available as Cool & Cold or Hot & Cold
- ✓ Designed to fit the Waterworks™ Twist & Turn Twin head Plumbed in filtration system
- ✓ Lead free Waterways
- ✓ Stainless steel Reservoir
- ✓ Vandal resistant Taps
- ✓ Available in Black only
- ✓ 36 Month Comprehensive Warranty

**3 YEAR
WARRANTY**

D26 SERIES

GENERAL FEATURES

The newest addition to our range of bottle top coolers, boasting the high level of quality Waterworks™ is renowned for. The D26 is sure to be a new favourite!

COLD TANK: 3.6 litre hygienic type 304 stainless steel for superior chilling. The highly polished surface is easy to clean and maintain.

HOT TANK: 1.8 litre type 304 stainless steel tank with 500 watt sheathed heater to ensure temperature control. The on/off switch is easily accessible at the back of the unit.

CABINET: Available in black only. The top and front panels are moulded UV treated ABS. The side panels are made from zinc coated steel sheets covered in polymer polyester resin.

TAPS: NSF Approved durable polypropylene self-closing design. Fully recessed, lever type for fast flow. Hot safety tap comes as standard on hot/cold model. Optional hygienic push taps also available.

OPTIONAL FILTRATION

EASY SWING, TWIST & TURN PLUMBED-IN FILTRATION

SEDIMENT CARTRIDGE - F-PNP-10-SED

Flow rate 2L per minute

5 Micron Polypropylene pre filter for the removal of dirt sediment, rust and particles.

Filter replacement - 1900L or 6 months. Which ever occurs first.

CARBON BLOCK - F-PNP-10-CARB-5MIC

5 Micron Silver impregnated carbon block for chemical, taste and odour removal.

Flow rate 2L per minute

Filter replacement - 1900L or 6 months. Which ever occurs first



Waterworks™ Australia

ABN 91 902 793 936

48-50 Neumann Road Capalaba Queensland 4157

Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled static type with no moving parts.

PERFORMANCE

Tap 1 Approx. 4-10°C

Tap 2 Room Temperature

Hot tap Approx. 84-89°C

CAPACITY

ROOM TEMP °C	21	27	32
150ML CUPS/HR 10°C	44	32	18
LITRES/HR AT 10°C	4.2	3.1	1.8
HOT WATER DELIVERY: 45 x 170ml cups per hour			

*Intermittent use only, continuous use will result in reduced performance.

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
B26C	17kg	B26CH	18kg	33cm	33cm	100cm

WARRANTY

The Waterworks™ D26 Series water coolers are covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.

Damage to the stainless steel tank may occur if using reverse osmosis or incorrect filtration.

Warranty will be void in the event of this happening.

Please discuss filtration options with your local water filter specialist.

Distributed by...

Awesome Water Mackay

www.awesomewatermackay.com

0401 441 291

Phone (07) 3390 3777

Email sales@waterworksaustralia.com

www.waterworksaustralia.com